

HI 733A-0 Nessler Reagent Safety Data Sheet

Canadian Regulation SOR/88-66

According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200

Revision Date: 2012-05-24 **Reason for Revision:** (1st edition)

SECTION 1: IDENTIFICATION OF THE PRODUCT AND COMPANY

Product Name: HI 733A-0 Nessler Reagent Additional Product Codes: HI 733-25

Application: Determination of Ammonia in Water Samples

Company Information (USA):

Hanna Instruments, Inc.

584 Park East Dr. Woonsocket, Rhode Island, USA 02895

Technical Service Contact Information: 1-800-426-6287 (8:30AM - 5:00PM ET)

+1-401-766-4260 (8:30AM - 5:00PM ET)

USA Emergency Contact Information: 1-800-424-9300 (Chemtrec 24Hr. Emergency)

International Emergency Contact Information: +1-703-527-3887 (Chemtrec 24Hr. Emergency)

E-mail Address: tech@hannainst.com

SECTION 2: HAZARD IDENTIFICATION

Toxic if swallowed. Fatal in contact with skin. Causes severe skin burns and eye damage. Toxic if inhaled. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

According to Regulation (EC) No. 1272/2008:

Classification: Acute Toxicity, Oral (Category 3)

Acute Toxicity, Dermal (Category 2) Acute Toxicity, Inhalation (Category 3) Skin Corrosion (Category 1A)

Specific Target Organ Toxicity, Repeated Exposure (Category 2)

Chronic Aquatic Toxicity (Category 2)

Signal Word: Danger

Pictograms:

S-phrases:



Hazard H301: Toxic if swallowed.

Statements: H310: Fatal in contact with skin.

H314: Causes severe skin burns and eye damage.

H373: May cause damage to organs through prolonged or repeated exposure.

H331: Toxic if inhaled.

H411: Toxic to aquatic life with long lasting effects.

Precaution P280: Wear protective gloves/protective clothing/eye protection/face protection. **Statements:** P301+P310: IF SWALLOWED: Immediately call a poison center or doctor/physician.

P307+P311: IF EXPOSED: Call a poison center or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower.

According to Directives 67/548/EEC and 1999/45/EC:

Symbol: T+: Very Toxic

C: Corrosive

N: Dangerous for the environment

R-phrases: 26/27/28-33-35-51/53: Very toxic by inhalation, in contact with skin and if swallowed. Danger of cumulative effects.

Causes severe burns. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 28-36/37/39-45-61: After contact with skin, rinse immediately with plenty of water. Wear suitable protective clothing,

gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Avoid release to the environment. Refer to special instructions safety data sheet.



Safety Data Sheet

According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

SECTION 3: COMPOSITION AND COMPONENT INFORMATION

FC No: CAS No: Hazard Class: Phrases: Component: Concentration:

7774-29-0 231-873-8 Acute Tox 1 H300, H310, H330, Mercury(II) iodide > 2% - < 10% Acute Tox 2 H373, H400, H410

STOT RE 2 R: 26/27/28-33-50/53 Aquatic Acute 1

Aquatic Chronic 1 T+, N

H314 Sodium hydroxide 215-185-5 1310-73-2 Skin Corr. 1A > 5% - < 20%

R: 35

FIRST AID MEASURES SECTION 4:

After Inhalation: Remove to fresh air. If necessary, apply mouth-to-mouth resuscitation or mechanical ventilation. Summon doctor.

After Skin Contact: Wash affected area with plenty of water. Immediately remove contaminated clothing.

After Eye Contact: Rinse out immediately with plenty of water and seek medical advice.

After Swallowing: Drink plenty of water (if necessary several liters), avoid vomiting (risk of perforation!). Immediately seek medical advice.

Do not attempt to neutralize.

General Information: Remove contaminated, soaked clothing immediately and dispose of safely.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Water spray, Carbon Dioxide, Dry Chemical Powder, Appropriate Foam.

Special Risks:

Development of hazardous combustion gases or vapors possible in the event of fire. Hydrogen may form upon contact with metals (danger of explosion!). The following may develop in event of fire: Mercury Vapors

Special Protective Equipment:

Do not stay in dangerous zone without suitable chemical protection clothing and self-contained breathing apparatus.

Additional Information:

Product itself is non-combustible. Cool container with spray water from a safe distance. Contain escaping vapors with water. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Do not inhale vapors/aerosols. Avoid substance contact. Ensure supply of fresh air in enclosed rooms.

Environmental Precautions:

Do not discharge into the drains/surface waters/groundwater.

Additional Notes:

None

SECTION 7: HANDLING AND STORAGE

Handling: Storage:

Avoid generation of vapors/aerosols. Work under hood.

Tightly closed. In a well-ventilated place at +15 to +25 °C. Protect from light. Accessible only for authorized persons. Do not inhale substance.



Safety Data Sheet

According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

SECTION 8:	<u>N 8:</u> EXPOSURE CONTROL/PERSONAL PROTECTION					
Туре	Value	Source		Туре	Value	Source
Mercury(II) loc	dide					
TWA (8hr)	0.025 mg (Hg)/m ³	Belgium		TWA (8hr)	0.025 mg (Hg)/m ³	Canada (Ontario)
TWA (8hr)	0.025 mg (Hg)/m ³	Canada (Quebec))	TWA (8hr)	0.1 mg (Hg)/m ³	France
TWA (8hr)	0.1 mg (Hg)/m ³	Germany		TWA (8hr)	0.1 mg (Hg)/m ³	Greece
TWA (8hr)	0.08 mg (Hg)/m ³	Hungary		TWA (8hr)	0.05 mg (Hg)/m ³	Poland
TWA (8hr)	0.025 mg (Hg)/m ³	Portugal		TWA (8hr)	0.025 mg (Hg)/m ³	Spain
TWA (8hr)	0.01 mg (Hg)/m ³	UK		TWA (8hr)	0.025 mg (Hg)/m ³	USA (ACGIH)
TWA (8hr)	2 mg (Hg)/m³	USA (OSHA)				
Sodium Hydro	oxide					
Ceiling	2 mg/m³	Belgium		Ceiling	2 mg/m³	Canada (Ontario)
Ceiling	2 mg/m³	Canada (Quebec))	TWA (8hr)	2 mg/m³	France
TWA (8hr)	2 mg/m³	Greece		TWA (8hr)	2 mg/m³	Hungary
TWA (8hr)	0.5 mg/m ³	Poland		Ceiling	2 mg/m³	Portugal
TWA (8hr)	1 mg/m³	Romania		Ceiling	2 mg/m³	Spain
TWA (15min)	2 mg/m³	UK		Ceiling	2 mg/m³	USA (ACGIH)
TWA (8hr)	2 mg/m³	USA (OSHA)				
Engineering	ı:					
ū	eneral industrial hygio otective Equipment	•				
	ctive gloves/clothing					
Respiratory Protection:			Protective Gloves:		Eye Protection:	
	hen vapors/aerosols Work under hood. ygiene:	are	Rubber or pla	stic		Goggles or face mask

SECTION 9: PHYSICAL/CHEMICAL PROPERTIES

Appearance: Yellowish liquid Odor: Odorless Density at 20°C: 1.28 g/cm3 **Melting Point:** ND **Boiling Point:** ND Solubility: Soluble pH at 20°C: Strongly basic Explosion Limit: NA Flash Point: NA

Thermal Decomp.: NA

SECTION 10: STABILITY AND REACTIVITY

Conditions to be Avoided: Hazardous Decomposition Products:

Heating In the event of fire: See section 5.

Hazardous Polymerization: Substances to be Avoided:

Immediately change contaminated clothing. Wash hands after working with substance.

Will not occur. Metals; light metals: could form hydrogen (risk of explosion)

Further Information:

Corrosive



Safety Data Sheet

According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

SECTION 11: TOXICOLOGICAL INFORMATION

Product Toxicity

Quantitative data on the toxicity of this product is not available.

Potential Health Effects:

Inhalation: After inhalation of aerosols: damage to the affected mucous membranes.

Severe burns with formation of scabs. Skin Contact:

Eye Contact: Burns, corneal lesion.

Severe pain (risk of perforation). Nausea, vomiting, and diarrhea. Ingestion:

Further Data: Further hazardous properties cannot be excluded. The product should be handled with the usual care when dealing

with chemicals

Component Toxicity

Chronic Toxicity: Acute Toxicity:

Not Available

Mercury(II) lodide

LD50: Oral - Rat - 18 mg/kg LD50: Dermal - Rat - 75 mg/kg

Additional Data:

mg/L

Systemic effects: mercury compounds have a cytotoxic and protoplasmatoxic effect. Intoxication symptoms: ACUTE: contact with eyes causes severe lesions. Swallowing and inhalation of dust damages mucous membranes of gastrointestinal and respiratory tract (metallic taste, nausea, vomiting, abdominal pain, bloody diarrhea, intestinal burns, glottal edema, aspiration pneumonia); drop in blood pressure, cardiac disrhythmia, circulatory collapse, and renal failure; CHRONIC: inflammation of the mouth with loss of teeth and mercurial line. The principal signs manifest themselves in the CNS (impaired speech, vision, hearing and sensitivity, loss of memory, irritability, hallucinations, delirium inter alia).

SECTION 12: ECOLOGICAL INFORMATION

Quantitative data on the ecological effect of this product is not available.

APPLICABLE TO PARTIAL COMPONENT:

The following applies to the water-soluble matter contained in inorganic Hg compounds in general (tested with mercury(II) chloride): Leuciscus idus LC50: 0.5 mg/L (48h), Daphnia magna EC50: 0.005-3,6 mg/L (48h), Chlorella pyrenoidosa EC50: 0.3 mg/L (5h), Pseudomonas fluorescens IC50: 0.005 mg/L. The toxicity of mercury(II) ions for water organisms depends on the water hardness [source: IPCS]. The following applies to iodides in general: biological effects: crustaceans: D. magna EC50: 2.7 mg/L; protozoa: E. sulcatum toxic as from 40

The following applies to sodium hydroxide: fish toxicity: LC50: 189 mg/L (1 N solution)

High aquatic toxicity. Harmful effect due to pH shift. Caustic even in diluted form. Endangers drinking water supplies if it Further Data:

enters in large quantities in soil and/or waters. Does not cause biological oxygen deficit. DO NOT ALLOW TO ENTER

WATERS, WASTE WATERS, OR SOIL!

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Chemical residues are generally classified as special waste and thus covered by local regulations. Contact local

authorities or disposal companies for advice. Handle contaminated packaging in the same way as the substance itself.

SECTION 14: TRANSPORTATION INFORMATION

Land (ADR/RID): Sea (IMDG): Air (ICAO/IATA):

2922 UN No.: 2922

Proper Shipping Name: Corrosive liquid, toxic, n.o.s. (sodium Corrosive liquid, toxic, n.o.s. (sodium

Corrosive liquid, toxic, n.o.s. (sodium hydroxide, mercuric iodide mixture) hydroxide, mercuric iodide mixture) hydroxide, mercuric iodide mixture)

Class (Sub Risk): 8 (6.1) 8 (6.1) 8 (6.1) **Packing Group:** Ш Ш Ш



Safety Data Sheet

According to Regulation (EC) No. 1907/2006 OSHA Regulation 29 CFR 1910.1200 Canadian Regulation SOR/88-66

SECTION 15: REGULATORY INFORMATION

Complies with European Regulations (EC) No. 1907/2006 and No. 1272/2008.

Complies with European Council Directives 67/548/EEC and 1999/45/EC.

Complies with OSHA Regulation 29 CFR 1910.1200.

Complies with Canadian Regulation SOR/88-66

SECTION 16: OTHER INFORMATION

Text of phrases under Section 3

R26/27/28: Very toxic by inhalation, in contact with skin and if swallowed.

R33: Danger of cumulative effects.

R35: Causes severe burns.

 ${\sf R51/53:}\ {\sf Toxic}\ {\sf to}\ {\sf aquatic}\ {\sf organisms},\ {\sf may}\ {\sf cause}\ {\sf long-term}\ {\sf adverse}\ {\sf effects}\ {\sf in}\ {\sf the}$

aquatic environment.

H300: Fatal if swallowed.

H310: Fatal in contact with skin.

H314: Causes severe skin burns and eye damage.

H373: May cause damage to organs through prolonged or repeated exposure.

H330: Fatal if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Revision Information

Revision Date: 2012-05-24

Supersedes edition of: (1st edition)

Reason for revision: (1st edition)

Legend NA: Not Applicable

ND: Not Determined

THE INFORMATION CONTAINED HEREIN IS BASED ON THE PRESENT STATE OF OUR KNOWLEDGE. IT CHARACTERIZES THE PRODUCT WITH REGARD TO THE APPROPRIATE SAFETY PRECAUTIONS. IT DOES NOT REPRESENT A GUARANTEE OF THE PROPERTIES OF THE PRODUCT.