

# MATERIAL SAFETY DATA SHEET

## Reef Builder

### Section I: MANUFACTURER'S NAME, ADDRESS, AND CONTACT INFORMATION

Seachem Laboratories, Inc.  
1000 Seachem Drive  
Madison, GA 30650

Emergency Telephone Number: 706-343-6060  
Telephone Number for Information: 706-343-6060  
Date Prepared: 06 July 2006

### SECTION II: CHEMICAL INGREDIENTS/IDENTITY INFORMATION

Components (Chemical Identity; Common Names (s))	OSHA PEL	ACGIH TLV	Other Limits
Proprietary blend of powdered carbonate, bicarbonate, chloride and sulfate salts of sodium, magnesium, calcium, strontium and potassium.	15 mg/m <sup>3</sup> total dust, 8 hour TWA	10 mg/m <sup>3</sup> inhalable dust, 8 hour TWA	NA
	5 mg/m <sup>3</sup> respirable dust, 8 hour TWA	3 mg/m <sup>3</sup> respirable dust, 8 hour TWA	

### SECTION III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	NA	Specific Gravity (H <sub>2</sub> O = 1)	ND
Vapor Pressure (mm Hg)	NA	Melting Point	ND
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water	Very soluble	Appearance and Odor	white odorless crystalline powder

### SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	NA
Flammable Limits	NA
LEL	NA
UEL	NA
Extinguishing Media	NA
Special Fire Fighting Procedures	NA
Unusual Fire and Explosion Hazards	NA

### SECTION V: REACTIVITY DATA

Stability	Stable under normal conditions of use
Conditions to Avoid	Incompatibilities
Incompatibility (Materials to Avoid)	Acids

Hazardous Decomposition or Byproducts	None
Hazardous Polymerization	Will Not Occur
Polymerization Conditions to Avoid	None

## SECTION VI: HEALTH HAZARD DATA

Route(s) of Entry: Eyes, skin, inhalation, ingestion
Health Hazards (Acute): Irritation of the eyes, skin, and respiratory tract. Ingestion of large doses may cause gastrointestinal distress and vomiting.
Carcinogenicity: NA
Signs and Symptoms of Exposure: ingestion-nausea, vomiting; skin, eyes-reddening and irritation; inhalation-coughing
Medical Conditions Generally Aggravated by Exposure: ND
Emergency and First Aid Procedures: Ingestion-Give several glasses of water to drink to dilute. If large amounts were swallowed, get medical advice. Skin, eyes-Flush with water for 15 minutes. Inhalation-Remove to fresh air.

## SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled: Dilute with water and flush to drain.
Waste Disposal Method: No special disposal method required, except that it be in accordance with current local authority regulations.
Precautions to Be Taken in Handling and Storing: Store dry until ready to use.
Other Precautions: All materials should be handled under good housekeeping practices.

## SECTION VIII: CONTROL MEASURES

Respiratory Protection	Recommended
Ventilation	Not required
Protective Gloves	Recommended
Eye Protection	Recommended
Other Protective Clothing or Equipment	None
Work/Hygienic Practices	Good housekeeping practices

## ABBREVIATIONS

ACGIH: The American Conference of Governmental Industrial Hygienists, Inc.

IARC: The International Agency for Research on Cancer

LEL: Lower Explosive Limit (or Lower Flammable Limit)

NA: Not Applicable

ND: Not Determined

NTP: The National Toxicology Program

OSHA: The Occupational Health and Safety Administration

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

TWA: Time Weighted Average

UEL: Upper Explosive Limit (or Upper Flammable Limit)

